

10/768,431

LUC-463/Barclay 12-10-6-9

CLAIM AMENDMENTS**RECEIVED
CENTRAL FAX CENTER****MAR 09 2007**

1 1. (Currently amended) An apparatus, comprising:
2 a network component that employs a) one or more call characteristics to make a
3 determination to initiate a request for one or more positions of one or more mobile
4 stations and b) one or more call parameters to identify one or more cellular network
5 cells associated with the one or more mobile stations;
6 wherein the network component receives, in response to the request, the one or
7 more positions of the one or more mobile stations from a position component; and
8 wherein the position component determines the one or more positions of the one
9 or more mobile stations continuously.

1 2. (Original) The apparatus of claim 1, wherein the network component
2 performs a comparison of the one or more call characteristics with one or more
3 thresholds to make the determination to initiate the request for the one or more
4 positions of the one or more mobile stations.

1 3. (Previously presented) The apparatus of claim 2, wherein the one or more
2 call characteristics comprise a pilot signal strength characteristic, and wherein the one
3 or more thresholds comprise a pilot signal strength threshold, and wherein the network
4 component performs a comparison of the pilot signal strength characteristic with the
5 pilot signal strength threshold;

10/768,431

LUC-463/Barclay 12-10-6-9

6 wherein the network component makes the determination to initiate the request
7 for the one or more positions of the one or more mobile stations based on a result of the
8 comparison of the pilot signal strength characteristic with the pilot signal strength
9 threshold.

1 4. (Original) The apparatus of claim 2, wherein the network component
2 employs the one or more call characteristics to create one or more call statistics,
3 wherein the one or more thresholds comprise one or more call characteristic thresholds
4 and one or more call statistic thresholds;

5 wherein the network component performs a comparison of the one or more call
6 statistics with the one or more call statistic thresholds;

7 wherein the network component employs a comparison of the one or more call
8 characteristics with the one or more call characteristic thresholds and the comparison of
9 the one or more call statistics with the one or more call statistic thresholds to make the
10 determination to initiate the request.

1 5. (Original) The apparatus of claim 2, wherein the network component
2 comprises an interface, wherein the network component receives the one or more
3 thresholds from a service provider through employment of the interface.

1 6. (Original) The apparatus of claim 1, wherein the network component
2 employs the determination to initiate the request to promote an avoidance of congestion
3 in one or more cellular network communication paths.

10/768,431

LUC-463/Barelay 12-10-6-9

1 7. (Previously presented) The apparatus of claim 6, wherein the network
2 component makes the determination to initiate the request upon an exceedance of the
3 one or more call characteristics relative to one or more thresholds;

4 wherein upon the exceedance of the one or more call characteristics relative to
5 the one or more thresholds, the network component and the position component
6 cooperate to obtain the one or more positions of the one or more mobile stations.

1 8. (Original) The apparatus of claim 7, wherein upon a termination of the
2 exceedance of the one or more call characteristics relative to the one or more
3 thresholds, the network component and the position component cooperate to
4 discontinue attainment of the one or more positions of the one or more mobile stations.

1 9. (Original) The apparatus of claim 1, wherein the network component
2 employs the one or more call characteristics to perform a selection of the one or more
3 mobile stations from a plurality of mobile stations;

4 wherein the network component employs the selection to formulate the request
5 for the one or more positions of the one or more mobile stations from the plurality of
6 mobile stations.

1 10. (Currently amended) The apparatus of claim 1, wherein the one or more
2 mobile stations are associated with the one or more cellular network cells; and

3 wherein the network component employs the one or more call characteristics to
4 perform a selection of the one or more cellular network cells from a plurality of cellular
5 network cells; and

10/768,431

LUC-463/Barclay 12-10-6-9

6 wherein the network component employs the selection to formulate the request
7 for the one or more positions of the one or more mobile stations that are associated with
8 the one or more cellular network cells.

1 11. (Original) The apparatus of claim 10, wherein the network component
2 employs a switch component to identify the one or more mobile stations that are
3 associated with the one or more cellular network cells;

4 wherein the network component employs the switch component to determine the
5 one or more positions of the one or more mobile stations that are associated with the
6 one or more cellular network cells.

1 12. (Original) The apparatus of claim 1, wherein the network component
2 receives the one or more positions of the one or more mobile stations in response to the
3 request;

4 wherein the network component employs the one or more positions of the one or
5 more mobile stations and the one or more call characteristics to develop a coverage
6 map.

1 13. (Original) The apparatus of claim 1, further comprising:

2 a switch component that provides the one or more call characteristics to the
3 network component;

4 wherein the network component employs the one or more call characteristics to
5 make a determination to initiate a request to the switch component;

6 wherein the switch component obtains the one or more positions of the one or
7 more mobile stations based on the request to the switch component.

10/768,431

LUC-463/Barclay 12-10-6-9

1 14. (Currently amended) The apparatus of claim 13, wherein the network
2 component provides to the switch component the one or more call parameters;

3 wherein the switch component employs the one or more call parameters to
4 perform an identification of the one or more mobile stations from a plurality of mobile
5 stations; and

6 wherein the switch component employs the identification of the one or more
7 mobile stations from the plurality of mobile stations to obtain the one or more positions
8 of the one or more mobile stations.

1 15. (Original) The apparatus of claim 14, wherein the one or more mobile
2 stations are associated with one or more calls;

3 wherein the switch component employs the one or more call parameters to
4 perform an identification of the one or more calls from a plurality of calls;

5 wherein the switch component employs the identification of the one or more calls
6 from the plurality of calls to obtain the one or more positions of the one or more mobile
7 stations that are associated with the one or more calls.

1 16. (Previously presented) The apparatus of claim 13, wherein the network
2 component and the switch component receive the one or more positions of the one or
3 more mobile stations from the position component;

4 wherein the network component and the switch component cooperate to develop
5 a coverage map through employment of the one or more positions of the one or more
6 mobile stations.

10/768,431

LUC-463/Barclay 12-10-6-9

1 17. (Original) The apparatus of claim 16, wherein the position component
2 employs one or more of an Enhanced Forward Link Trilateration algorithm and an IS-
3 801 solution using an Assisted Global Positioning System (AGPS), Advanced Forward
4 Link Trilateration (AFLT) or combined AGPS/AFLT algorithm to determine the one or
5 more positions of the one or more mobile stations.

1 18. (Currently amended) A method, comprising the steps of:
2 initiating a request for one or more positions of one or more mobile stations
3 through employment of a) one or more call characteristics and b) one or more call
4 parameters to identify one or more cellular network cells associated with the one or
5 more mobile stations;
6 receiving, in response to the request, the one or more positions of the one or
7 more mobile stations; and
8 determining the one or more positions of the one or more mobile stations
9 continuously.

1 19. (Original) The method of claim 18, wherein the step of initiating the
2 request for the one or more positions of the one or more mobile stations through
3 employment of the one or more call characteristics comprises the steps of:
4 performing a comparison of the one or more call characteristics with one or more
5 thresholds; and
6 initiating the request for the one or more positions of the one or more mobile
7 stations based on the comparison.

10/768,431

LUC-463/Barclay 12-10-6-9

1 20. (Currently amended) The method of claim 19, wherein the step of
2 initiating the request for the one or more positions of the one or more mobile stations
3 based on the comparison comprises the steps of:

4 determining the one or more call parameters associated with the one or more
5 thresholds;

6 identifying the one or more mobile stations from a plurality of mobile stations
7 through employment of the one or more call parameters; and

8 initiating the request for the one or more positions of the one or more mobile
9 stations through employment of the one or more call parameters.

1 21. (Currently amended) An article A computer-readable medium having
2 computer executable instructions for performing steps, comprising:

3 one or more computer-readable signal-bearing media;

4 means in the one or more media for initiating a request for one or more positions
5 of one or more mobile stations through employment of a) one or more call
6 characteristics and b) one or more call parameters to identify one or more cellular
7 network cells associated with the one or more mobile stations.

1 22. (Previously presented) The apparatus of claim 16, wherein the
2 position component is pre-provisioned with one or more intervals of time to determine
3 the one or more positions of the one or more mobile stations.

1 23. (New) The apparatus of claim 5, wherein the thresholds provide a
2 measure of a quality level of service provided to the one or more mobile stations.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.